



KÉTRÉSZES SZORÍTÓBILINCSEK

Típus:

Kétrészes szorítóbilincs

Szabvány:

EN 14420-3 / DIN 2817

Csavar: DIN912 / EN ISO 4762 8.8

Anya: DIN 934 / EN ISO 4032

Üzemi nyomás:

-0,8bar - 25bar



Névleges átmérő	Tömlő mérete	Tömlő külső átmérője	Alumínium	Rozsdamentes
mm	mm	mm	Cikkszám	
15	13x5	22-24	RK013	RKR013
20	19x6	30-33	RK019	RKR019
25	25x5	34-36	FRK025005	-
25	25x6	36-39	RK025	RKR025
32	32x5	41-43	FRK032005	-
32	32x6	43-46	RK032	RKR032
40	38x5	47-49	FRK038005	-
40	38x6,5	53-52	RK038	RKR038
50	50x5	59-61	FRK050005	FRKR050005
50	50x8	63-67	RK050	RKR050
50	50x10	69-71	RK050010	-
65	63x6	74-76	FRK063006	FRKR063006
65	63x8	78-82	RK063	RKR063
80	75x6	86-88	FRK075006	FRKR075006
80	75x8	89-93	RK075	RKR075
80	75x10	94-97	RK075010	-
100	100x6,5	112-114	FRK100065	-
100	100x8	114-119	RK100	RKR100
100	100x10	118-122	RK100010	-
125	125x10	143-148	RK125	-
150	150x12	167-173	RK150	-
200	200x12	222-229	RK200	-

További rendelhető tömlőbilincs:



Kétrészes szorítóbilincs réz alapanyagból